



Dimensions





Door leaf width (1 door leaf)	500 mm up to 1125 mm
Door leaf height	up to 2500 mm

System description

Our sound insulation door ATB 42 consists of a mitered door leaf of circumferential aluminium tubular frame. The system got a glass filling of safety glass and is available as single glazing in single leaf or double leaf performance. The ATB 42 is a flush door leaf.

Installation options

- Solid wall
- Plasterboard partitions
- Lindner partition systems

	Technical data
Thickness of the door leaf	42mm
Weight of the door leaf	approx. 24 - 35 kg/m ²
Profile width of the door leaf; circumferential	95 mm
	Sound insulation
ISO 717-1	◦ single leaf up to 37 dB Rw (=laboratory value)
	Standard equipment
Barrel door-hinge 160 mm with VX inclusion	Mortise lock for a tubular frame door leaves; Class 3; prepared for profile and round cylinders
automatically lowerable bottom seal	on both sides offset door handle
	Additional equipment / Options
superimposed or integrated door closers	Fitting combinations for emergency exit doors and panic bolts
Access control	Monitoring contacts
etc. according to the demands and the customer requests	

Surfaces of the profiles

- E6/C0 anodised aluminium
- Powder- coated aluminium in RAL- and NCS-colours

Glass design

- Clear glass
- Low iron glass

Door frame

- Aluminium door frame
- Steel door frame (one- or two-piece)
- Wooden door frame

Information on Lindner Group



and its related logo, is a trademark owned by the U.S. Green Building Council ®

Specific solutions are project- related possibly

- standard
- optional

Further information can be found on our homepage www.Lindner-Group.com



Subject to change without notice. This document is our intellectual property. It may neither be duplicated, exploited for profit, distributed for business purposes nor shown to any third parties without our approval.