



Round and suspended luminaire, equipped with LED technology.

The circumferential indirect lighting causes a soft ceiling illumination.

Light is distributed via an opal acrylic cover.

Housing is made of sheet steel, colour acc. to RAL 9016.

Electrical connection area on rear side is slightly raised.

Type	Lumen Output	System Power	Dimension (Ø x h)
FLAT C-p 300 1.5 OS	1.760 Lumen	15 Watt	300 x 75 (53+22) mm
FLAT C-p 360 3.5 OS	3.520 Lumen	30 Watt	360 x 75 (53+22) mm
FLAT C-p 470 4.0 OS	4.210 Lumen	36 Watt	470 x 75 (53+22) mm
FLAT C-p 600 5.5 OS	5.600 Lumen	48 Watt	600 x 75 (53+22) mm
FLAT C-p 900 8.0 OS	8.460 Lumen	57 Watt	900 x 75 (53+22) mm
FLAT C-p 1200 12.0 OS	12.180 Lumen	84 Watt	1.200 x 75 (53+22) mm

Technical Information:

Voltage:	220-240 V / 50-60 Hz
Protection Class:	1
Protection Type:	IP20
Ballast:	switchable
Cover:	opal
Colour:	RAL 9016
Light Colour:	4.000K
CRI:	RA>80

Options:

- Light Colour 3.000K
- Ballast DALI dimmable
- Housing acc. to RAL Card
- Microprismatic cover (BWF)
- Microprismatic cover UGR<19 (Jungbecker)

Dimension Drawing:

