



Exemplary illustration  
The Type 4.5 has four instead of six LED modules

LED recessed light suitable for all common ceiling systems (exception Clip K3). Frameless and jointless light cover with a glass diffuser and white edge.

Design with unique LED/reflector system and highly efficient all-round glare-free wide-beam light technology (UGR<19). Specially designed for use with high ceilings and/or higher light intensities.

The narrow installed height of 55 mm saves a lot of space.

Seamless closed-cell seal between housing and frame.

Inspection by opening retaining knob.


Type	Lighting system	Approx. size
LP 625 (600) LED-U3 4.5 AG	LED 840, 4530 Lm, ca. 31W	625x625x55 mm (600x600x55)
LP 625 (600) LED-U3 6.5 AG	LED 840, 6800 Lm, ca. 47W	625x625x55 mm (600x600x55)
LP 625 (600) LED-U3 7.5 AG	LED 840, 7860 Lm, ca. 55W	625x625x55 mm (600x600x55)
LP 1200x300 LED-U3 6.5 AG	LED 840, 6800 Lm, ca. 47W	1200x300x55 mm

\*plus cable connection


**Technical Data:**

- Voltage: 220-240 V / 50-60 Hz
- Protection class: 1
- Protection rating: IP65, IP50 on back side
- Control unit: switchable, optional DALI dimmer
- Elec. connection: internal 3-pin plug (DALI 5-pin) with straight wiring option
- Colour: RAL 9016 / customer choice
- Glass: toughened safety glass

**Light distribution curve:**



**Scale diagram:**



**Options:**

- emergency light
- elec. connection according to customer requirement
- operable from above (TOP type)
- cover glass with black edge