



T30-1 Typ I-HRT

Fire protection door

Wood framed door leaf, approx. 68 mm single door leaf with fire protection T30 (Smoke control, sound insulation, burglary resistance, moisture resistance on demand).

datasheet.headline.technischeAnforderungen.title

Fire Protection: Fire Resistance, Smoke Protection

Design: Wood, Varnish, Laminate **Acoustics:** Airborne Sound Reduction

Hygiene: Cleanable by vacuuming, Wipeable, Antibacterially disinfectable, Virucide

disinfectable

Safety Technology: Intruder Protection





The mark of responsible forestry

Dimensions

Door leaf thickness	approx. 68 mm mm
Width	500 - 1 500 mm
Height	1 750 - 3 000 mm
Height incl. Top panel	4 000 mm

Technical Details

Climate class	DIN EN 12219		2		
mechanischeBeanspruchung_Wert	group E				
Installation options	Drywall, Lindner partition systems, Solid walls				
Edge design (door leaf)	RAL-/NCS coated edge , Solid wood edge band, Solid wood inset edge band				
Frame type	Wooden block frame, Solid wooden frame, Wooden enclosing frame,				
Glazing					
Number of leaves		single-leaf			
Standard					
Additional					
Door leaf weight		44 kg/m²			





Acoustics

objectbrick.Akustik.Bauakustik.title						
Weighted sound reduction index		N EN ISO 0140-2	R _w		43 dB	
Fire protection						
objectbrick.Brandschutz.Feuerwiderstand.title						
Resistance to fire performance	DI	DIN 4102-5		T 30		
objectbrick.Brandschutz.Rauchdichtigkeit.title						
smoke protection	DI	DIN 18095		RS		
Safety						
objectbrick.Sicherheitstechnik.Einbruchschutz.	title					
Burglar resistance	DI	DINV ENV 1627		WK2, WK3		
Burglar resistance	DI	DIN EN 1627		RC1, RC2		
Durability						
Suitable for use in moisture-room	m	moisture resistant				
Surfaces						
Surfaces	rea	real wood veneer, , ,				
Sustainability						
deklarationen_und_nachweise						

Sustainable