



## T0-1 Typ A

### Object door

Door leaf, approx. 41 mm with laminated intermediate layer and strengtheners of oriented strand board, single door leaf without fire protection (sound insulation, radiation protection, moisture resistance on demand).

#### **datasheet.headline.einsatzgebiete.title**

**Work:** Common Rooms, Facilities for Meetings, Conventions and Conferences, Office buildings, Data Centres, Broadcasting Rooms, Television Studios, Utility Rooms, Assembly Rooms

**Businesses, Recreation and Culture:** Banks, Concert Halls, Shopping Centres, Cinemas and Theatres, Museums, Public Swimming Pools, Gymnasiums, Stadiums, Places of Assembly

**Education:** Library Rooms, Research Rooms, Schools, School of Higher Education

**Healthcare:** Pharmacies (Production), Clinics and Hospitals, Laboratories and Research Facilities, Clean rooms ( pharmacy and medical technology)

**Hotels and Gastronomy:** Restaurants and Canteens, Commercial Kitchens, Hotels and Resorts

**Industry:** Laboratories and Research Facilities, Production Facilities, Clean rooms (electronics and semiconductor technology)

**Transport:** Train Stations, Airports

**Public Areas:** Entrance Areas, Escape Routes

**Public Institutions:** Court Houses, Government Buildings, Court Houses, Government Buildings

**Residential**



#### **datasheet.headline.technischeAnforderungen.title**

**Design:** Wood, Varnish, Laminate

**Acoustics:** Airborne Sound Reduction

**Sustainability:** Environmental Product Declaration

**Hygiene:** Cleanable by vacuuming, Wipeable, Antibacterially disinfected, Virucide disinfected

### Dimensions

Door leaf thickness	approx. 41 mm mm
Width	500 - 1 250 mm
Height	625 - 2 500 mm
Height incl. Top panel	3 500 mm

### Technical Details

Climate class	DIN EN 12219	2
mechanischeBeanspruchung_Wert	group S	
Installation options	Solid walls, Drywall, Lindner partition systems	



Edge design (door leaf)	PU-edge, Plastic edge band, RAL-/NCS coated edge , Solid wood edge band, Solid wood inset edge band
Frame type	Wooden block frame, Aluminium frame, Wooden enclosing frame, Solid wooden frame, Steel frame (one-piece), Steel frame (two-piece)
Glazing	, Circular glazing, , Special shapes
Number of leaves	single-leaf

### Standard

### Additional

Door leaf weight	26 kg/m <sup>2</sup>
------------------	----------------------

### Acoustics

#### objectbrick.Akustik.Bauakustik.title

Weighted sound reduction index	DIN EN ISO 10140-2	R <sub>w</sub>	32 dB
--------------------------------	--------------------	----------------	-------

### Safety

#### objectbrick.Sicherheitstechnik.Strahlenschutz.title

Radiation protection	DIN 6834	lead equivalent value 2 mm Pb
----------------------	----------	-------------------------------

### Durability

Stress group	DIN EN 1192	S
Suitable for use in moisture-room	moisture resistant	
Suitable for use in wet-room	capable for wet rooms	

### Sustainability

#### Evidence of emission measurements

Indoor Air Comfort	Fulfills
Indoor Air Comfort Gold	Fulfills
AgBB	Fulfills
BREEAM International	Conform



---

LEED v4	Conform
DGNB	Conform

---

**deklarationen\_und\_nachweise**

---

**Product**

---

**Sustainable**

---

**Emission**

---