



# RIBline Timber Slats Ceiling

## Cladding system

### **datasheet.headline.einsatzgebiete.title**

**Businesses, Recreation and Culture:** Banks, Shopping Centres, Cinemas and Theatres, Concert Halls, Museums, Public Swimming Pools, Gymnasiums, Stadiums, Sales Areas, Places of Assembly

**Education:** Library Rooms, Research Rooms, School of Higher Education, Schools, Teaching, Class and Educational Rooms

**Work:** Common Rooms, Facilities for Meetings, Conventions and Conferences, Stage and Studio Rooms, Office buildings, Film- & Recording Studios, Data Centres, Broadcasting Rooms, Television Studios, Utility Rooms, Assembly Rooms, Administration Buildings

**Healthcare:** Pharmacies (Production), Clinics and Hospitals, Laboratories and Research Facilities, Operating Theatres, Clean rooms ( pharmacy and medical technology)

**Transport:** Airports, Train Stations

**Hotels and Gastronomy:** Restaurants and Canteens, Commercial Kitchens, Hotels and Resorts

### **datasheet.headline.technischeAnforderungen.title**

**Design:** Gypsum

**Fire Protection:** Fire Behaviour / Building Material Class

**Corrosion Protection:** Interiors

**Hygiene:** Cleanable by vacuuming, Wipeable

## Technical Details

---

**Material:** Recycled Gypsum Core

**Surface:** Wood Veneer Laminate

### **System weight:**

Solo – Approx. 2-3 kg/m<sup>2</sup> (excluding substructure)

Panel – Approx. 11-14 kg/m<sup>2</sup> (excluding substructure)

**Mounting and Demounting:** Hook-in and Slide options

**Temperature:** 15°-23°C

## Dimensions

---

### **RIBline Ceiling Solo**

**Type:** Solo

**Length (L):** up to 2,500 mm

**Thickness (T):** 38 mm

**Height (H):** 22 mm, 38 mm, 54 mm, 65 mm, 70 mm

**Spacing:** 100 mm, 125 mm, 140 mm



## RIBl ine Ceiling Panel

**Type:** Panel

**Length (L):** 600-1,200 mm

**Width (W):** 300-600 mm

**Thickness of Lamella (T):** 18 mm, 22 mm

*Please note: Bespoke size and dimension possible upon request. Reachout to RIBl ine team to find a perfect fit for your project.*

## Fire protection

### objectbrick.Brandschutz.Baustoffklasse.title

Building material class	DIN EN 13501-1	B - s1,d0
-------------------------	----------------	-----------

## Durability

Stress class	DIN EN 13964	A
--------------	--------------	---

## Surfaces

### Wood Veneers:

Natural Wood Veneer\*

Engineered Wood Veneer\*

*\*FSC Certified Veneer upon request*

### Laminates:

Continous Pressed Laminates (CPL)

High Pressure Laminates (HPL)

## Sustainability

### Evidence of emission measurements

CO2 Einsparung	%
CO2 Bilanz	kg/m <sup>2</sup>
Gaseinsparung	%
Wassereinsparung	%