



Lindner Plus - Facade connections

Lindner Facade connections, which are factory-made pre-assembled, ensure a perfect connection between the facade and your partition or plasterboard wall. With its slim support profiles, which are available in various surface finishes, they offer even visually enough possibilities to design your room individually.

Examples for areas of application

Work: Facilities for Meetings, Conventions and Conferences, Office buildings, Common Rooms, Assembly Rooms

Education: Research Rooms, Schools, School of Higher Education, Teaching, Class and Educational Rooms

Industry: Production Facilities

Technical details

Technical data

Combined wall panels	Trockenbauwände
Tolerances	object-related planning

Dimensions

Dimensions

Height	3000 mm
Axis grid	990 mm
Wall thickness	28 - 64 mm

Acoustics

Building acoustics

DIN EN ISO 717 1 2	DIN EN ISO 717 2 abhängig Zusatzmaßnahmen	R_w	52 dB
--------------------	---	-------	-------

Fire protection

Fire resistance

Fire resistance	DIN 4102-2	F 30 F 90
-----------------	------------	--------------

Static

Statics

Installation area	DIN 4103 1	Installation area 1 & 2
-------------------	------------	-------------------------



Surfaces

Surfaces

Surfaces	Real wood veneer Anodized coating Glas Powder coated
----------	---

Sustainability

Evidence

BREEAM International	Conform
LEED v4	Conform
DGNB	Conform