





## BASICline

### Standard Perforations


The standard perforations BASICline are common perforations that are constantly available. The round holes can be arranged in straight pitch or in diagonal pitch (45° or 60°). Perforated metal ceilings are acoustically effective when combined with sound-absorbing inlays on the rear side.

- round holes arranged in straight pitch or in diagonal pitch (45° or 60°)
- acoustically effective in combination with sound absorbing inlays




### Variants

#### Rg 2,5 - 4


Surface	<ul style="list-style-type: none"> <li>• hole: Ø 2.5 mm straight pitch</li> <li>• open area: 4 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1,400 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1,400 mm</li> </ul>	
---------	---	---

#### Rd 2,5 - 8


Surface	<ul style="list-style-type: none"> <li>• hole: Ø 2.5 mm diagonal pitch</li> <li>• open area: 8 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1,400 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1,400 mm</li> </ul>	
---------	---	---

#### Rg 2,5 - 16




Surface	<ul style="list-style-type: none"> <li>• hole: Ø 2.5 mm straight pitch</li> <li>• open area: 16 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1,400 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1,400 mm</li> <li>• material: aluminium   thickness: 0.8 mm   width of perforation: 790 mm</li> </ul>	
---------	--	---


### Rg 3,0 - 4

Surface	<ul style="list-style-type: none"> <li>• hole: Ø 3.0 mm straight pitch</li> <li>• open area: 4 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1.540 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1.540 mm</li> </ul>	
---------	---	---

### Rv 3,0 - 5


Surface	<ul style="list-style-type: none"> <li>• hole: Ø 3.0 mm diagonal pitch</li> <li>• open area: 5 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1,500 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1,500 mm</li> </ul>	
---------	---	---

### Rg 3,0 - 17


Surface	<ul style="list-style-type: none"> <li>• hole: Ø 3.0 mm straight pitch</li> <li>• open area: 17 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1,540 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1,540 mm</li> <li>• material: aluminium   thickness: 0.7 mm   width of perforation: 650 mm</li> </ul>	
---------	--	---

### Rv 3,0 - 20




Surface	<ul style="list-style-type: none"> <li>• hole: Ø 3.0 mm diagonal pitch</li> <li>• open area: 20 %</li> <li>• material: steel I thickness: 0.6 mm I width of perforation: 1,500 mm</li> <li>• material: steel I thickness: 0.7 mm I width of perforation: 1,500 mm</li> </ul>	
---------	--	---


### Rg 7,0 - 27

Surface	<ul style="list-style-type: none"> <li>• hole: Ø 7.0 mm straight pitch</li> <li>• open area: 27 %</li> <li>• material: steel I thickness: 0.6 mm I width of perforation: 1,300 mm</li> <li>• material: steel I thickness: 0.7 mm I width of perforation: 1,300 mm</li> </ul>	
---------	--	---

### Rv 7,0 - 30


Surface	<ul style="list-style-type: none"> <li>• hole: Ø 7.0 mm diagonal pitch</li> <li>• open area: 30 %</li> <li>• material: steel I thickness: 0.6 mm I width of perforation: 1,300 mm</li> <li>• material: steel I thickness: 0.7 mm I width of perforation: 1,300 mm</li> </ul>	
---------	--	---

### Rg 12,0 - 11


Surface	<ul style="list-style-type: none"> <li>• hole: Ø 12.0 mm straight pitch</li> <li>• open area: 11 %</li> <li>• material: steel I thickness: 0.6 mm I width of perforation: 1,290 mm</li> <li>• material: steel I thickness: 0.7 mm I width of perforation: 1,290 mm</li> </ul>	
---------	---	---

### Rd 12,0 - 22



Surface	<ul style="list-style-type: none"> <li>• hole: Ø 12.0 mm diagonal pitch</li> <li>• open area: 22 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1,290 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1,290 mm</li> </ul>	
---------	---	---

## Rg 12,0 - 44

Surface	<ul style="list-style-type: none"> <li>• hole: Ø 12.0 mm straight pitch</li> <li>• open area: 44 %</li> <li>• material: steel   thickness: 0.6 mm   width of perforation: 1,290 mm</li> <li>• material: steel   thickness: 0.7 mm   width of perforation: 1,290 mm</li> </ul>	
---------	---	---

## Technical details

### Types of perforation patterns

- Rg: Round holes arranged in straight pitch
- Rd: Round holes arranged in diagonal pitch (45°)
- Rv: Round holes arranged in diagonal pitch (60°)

### Example

Rg 2,5 - 16

- Rg: Round holes arranged in straight pitch
- 2,5: Hole diameter 2.5 mm
- 16: Open area 16 %

## Acoustics

Equipped with acoustic inlays, perforated surfaces achieve very high sound absorption values

## Fire protection

### Building material class

Fire behavior	DIN EN 13501-1	A2 - s1,d0
Flammability	ASTM E 84	class A

## Durability

### Durability

Exposure class	DIN EN 13964	A
----------------	--------------	---



## Sustainability

---

### Declarations

Product Self-Declaration	Self-Declaration according to ISO 14021
EPD (Environmental Product Declaration)	EPD according to EN 15804 / ISO 14025
circular economy	Cradle to Cradle Certified® Gold