



## T0-2 Typ W

### Sliding door

Sliding door leaf, approx. 41 mm or 49 mm with laminated intermediate layer and strengtheners of oriented strand board, double door leaf without fire protection (moisture resistance and radiation protection on demand).

#### Areas of application

**Work:** Common Rooms, Facilities for Meetings, Conventions and Conferences, Assembly Rooms, Office buildings

**Education:** Research Rooms, School of Higher Education, Schools, Teaching, Class and Educational Rooms

**Businesses, Recreation and Culture:** Places of Assembly

**Healthcare:** Clinics and Hospitals

**Industry:** Production Facilities, Laboratories and Research Facilities

**Public Institutions:** Court Houses, Government Buildings

**Residential**



The mark of responsible forestry

#### Technical requirements

**Design:** Wood, Varnish, Laminate

**Acoustics:** Airborne Sound Reduction

**Safety Technology:** Radiation Protection

**Hygiene:** Cleanable by vacuuming, Wipeable, Antibacterially disinfected, Virucide disinfected

#### Dimensions

##### product-detail-page.headline.getAbmessungenTueren

Door leaf thickness	approx. 41 mm, approx. 49 mm
---------------------	------------------------------

##### product-detail-page.headline.getAbmessungen

Width	1 000 - 3 000 mm
Height	625 - 2 750 mm

#### Technical Details

Climate class	DIN EN 12219	2
mechanischeBeanspruchung_Wert	group E group S	
Installation options	Drywall Lindner partition systems Solid walls	
Edge design (door leaf)	PU-edge Solid wood inset edge band Solid wood edge band	



	RAL-/NCS coated edge Plastic edge band
Frame type	Wooden enclosing frame
Glazing	Circular glazing Special shapes
Number of leaves	double-leaf
Door leaf weight	26 - 27 kg/m <sup>2</sup>

## Safety

### Radiation

Radiation protection	DIN 6834	lead equivalent value 2 mm Pb
----------------------	----------	-------------------------------

## Durability

Suitable for use in moisture-room	moisture resistant
Suitable for use in wet-room	capable for wet rooms

## Surfaces

Surfaces	Real wood veneer, , ,
----------	-----------------------

## Sustainability

### Indicators

Emission of formaldehyde	< 3 µg/m <sup>3</sup>
--------------------------	-----------------------

### Evidence of emission measurements

Indoor Air Comfort	Fulfills
Indoor Air Comfort Gold	Fulfills
AgBB	Fulfills
BREEAM International	Conform
LEED v4	Conform
DGNB	Conform

## Declarations

### Emission



---

**Sustainable**