



T0-2 Typ W

Sliding door

Sliding door leaf, approx. 41 mm or 49 mm with laminated intermediate layer and strengtheners of oriented strand board, double door leaf without fire protection (moisture resistance and radiation protection on demand).

Examples for areas of application

Work: Common Rooms, Facilities for Meetings, Conventions and Conferences, Assembly Rooms, Office buildings

Education: Research Rooms, School of Higher Education, Schools, Teaching, Class and Educational Rooms

Businesses, Recreation and Culture: Places of Assembly

Healthcare: Clinics and Hospitals

Industry: Production Facilities, Laboratories and Research Facilities

Public Institutions: Court Houses, Government Buildings

Residential



The mark of responsible forestry

Technical details

Technical data

DIN EN 12219	DIN EN 12219	2
mechanical stress		group E group S
Installation options		Drywall Lindner partition systems Solid walls
Edge design (door leaf)		PU-edge Solid wood inset edge band Solid wood edge band RAL-/NCS coated edge Plastic edge band
Frame type		Wooden enclosing frame Stahlzarge (ein-, zweiteilig)
Glazing		Circular glazing Friesbreite 135 mm Friesbreite min. 110 mm Special shapes



Number of leaves		double-leaf
Door leaf weight		26 - 27 kg/m ²
max. surface load		26 kg/m ²

Dimensions

Dimensions

Width (B)	1000 - 3000 mm
Height	625 - 2750 mm
Door leaf thickness	approx. 41 mm approx. 49 mm

Safety

Security

DIN 6834	DIN 6834 mmPb	lead equivalent value 2 mm Pb
----------	---------------	-------------------------------

Durability

Durability

Suitability for wet rooms	moisture resistant
Suitability for wet rooms	capable for wet rooms

Surfaces

Surfaces

Surfaces	Real wood veneer HPL-Schichtstoff RAL-/NCS-Nasslackierung bauseitiger Anstrich/Grundierfolie
----------	---

Sustainability

Declarations

Emission report	A report concerning VOC emissions of this product is available. Eurofins Product Testing A/S, an independent testing institute, performed the tests. The testing laboratory is ISO 17025 accredited and EN 16516 notified. For further information, please do not hesitate to contact us.
-----------------	---



Sustainable forestry

Our products can be supplied FSC-certified (Chain of custody) and meet all necessary requirements.
Certificate no.: TUEV-COC-000515 Licence no.: FSC-C119815

Key figures

Formaldehyde emissions	< 3 µg/m ³
------------------------	-----------------------

Evidence

Indoor Air Comfort	Accomplished
Indoor Air Comfort Gold	Accomplished
AgBB	Accomplished
BREEAM International	Conform
LEED v4	Conform
DGNB	Conform