



### Areas of application

- Office and conference rooms
- Industrial and factory areas
- Training and research facilities

### Construction options

- Double glazing
- 100 mm fully glazed partition
- 125 mm fully glazed partition

### Combinable with

- Lindner Logic 100 Metal / Timber
- Lindner Logic 100 Metal / Timber-Acoustic
- Lindner Plus Organisation
- Lindner Plus Blinds
- Doors for partition systems

### Description

System Lindner Life Freeze 137, with flush-mounted, bonded glazing, brings a sense of transparency and space into the room. Additionally, venetian blinds can be easily integrated into either the powder-coated or the anodised aluminium frames.

	<b>Dimensions</b> (depending on material used)	
	Module width	Standard up to 1500 mm
	Height	Standard up to 5000 mm / undivided 3500 mm
	<b>Please note:</b>	<b>The maximum wall height and the maximum module width can differ depending on the building physics!</b>
	Wall thickness	100 and 125 mm
	Joint width	6 mm (optionally 8 mm)
	<b>Technical data</b>	
	Weight	approx. 37 - 129 kg / m <sup>2</sup>
	Tolerances	± 10 mm in height and width
	Structural performance	<ul style="list-style-type: none"> <li>• Installation area 1 and 2</li> </ul> non load-bearing partition wall according to DIN 4103 Fall protection according to DIN 18008-4 and AbP (acc. to LBO and MVV TB)
	Bonding	<ul style="list-style-type: none"> <li>• according to ETAG 002</li> </ul> Permissible temperature range: -50°C - +150°C Colour: white / light grey / black General technical approval
	<b>Fire resistance</b>	
	DIN 4102	F0/ F30
	EN 13501-2	EI0/ EI30 / EI60
	<b>Sound insulation</b>	
	ISO 717-1	up to 57 dB R <sub>w</sub> (=laboratory value)
	<b>Longitudinal sound insulation</b>	
	ISO 717-1	up to 65 dB D <sub>n,f,w</sub>
	<b>Seismic safety</b>	anti-seismic performance possible
	<b>Guidelines</b>	Lindner visual assessment criteria for glazing systems

### Build connections

- **Connection accessories:** depending on the system stud used, hidden hooks are installed into the vertical shadow gaps at modular centres for the Lindner Plus organisation system
- **Joint seals:** seals are installed on the floor, ceiling and support profiles
- **Connections:** relocatable floor, ceiling and wall connections

### Substructure

- Steel studs, constructed from folded or rolled steel sheet profiles, zinc coated or laquered

### Applicable standards

- DIN 4103
- DIN 18008-4
- DIN 4102
- EN 13501-2
- ISO 717-1

### Surface finish

- powder-coated
- anodized

Subject to change without notice. This document is our intellectual property. It may neither be duplicated, exploited for profit, distributed for business purposes nor shown to any third parties without our approval.

Customised, project-specific solutions possible

Further information can be found on our homepage [www.Lindner-Group.com](http://www.Lindner-Group.com)

