



Dimensions

Door leaf width	1200 mm up to 1560 mm
Door leaf height	up to 2500 mm





System description

Door leaf made of aluminum tubular frame, mitered circumferential, with glass filling made of safety glass as single glazing in 1-leaf design. Available with or without sound insulation.

Installation options

Lindner partition systems

Subject to change without notice. This document is our intellectual property. It may neither be duplicated, exploited for profit, distributed for business purposes nor shown to any third parties without our approval.

	Technical data	
	Thickness of the door leaf	42mm
	Weight of the door leaf	approx. 24 - 35 kg/m ²
	Load capacity drive	max. 150 kg
	Sound insulation	
	ISO 717-1	● up to 37 dB R _w (=laboratory value)
	Standard equipment	
	Drive set in E6/C0 anodized, including cover caps and stoppers	
	Circumferential sealing system in E6/C0 anodized and grey sealing profiles	
	Threshold made of stainless steel	
	Handle bars made of stainless steel	
	Additional equipment / Options	
	Running rail with retraction dampening	
	Locking	
	etc. according to the demands and the customer requests	

Surfaces of the profiles

- E6/C0 anodised aluminium
- Powder-coated aluminium

Glass design

- Clear glass
- Low iron glass

Door frame

- Aluminium door frame
- Steel door frame

Information on Lindner Group



Customised, project-specific solutions possible

- standard
- optional

and its related logo, is a trademark owned by the U.S. Green Building Council ©

Further information can be found on our homepage www.Lindner-Group.com

