



Dimensions

Door leaf width	1200 mm up to 1560 mm
Door leaf height	up to 2500 mm





System description

Door leaf, approx. 41 mm with laminated intermediate layer and strengtheners of oriented strand board, single door leaf without fire protection. Available with or without sound insulation.

Installation options

Lindner partition systems

Technische Änderungen auch ohne Ankündigung vorbehalten. Diese Unterlage ist unser Geistiges Eigentum. Sie darf ohne unsere Zustimmung weder vervielfältigt, noch unbefugt verbreitet oder weiteren Personen vorgelegt werden.

	Technical data	
	Thickness of the door leaf	41 mm
	Weight of the door leaf	approx. 26 kg/m ²
	Load capacity drive	max. 150 kg
	Sound insulation	
	ISO 717-1	• up to 37 dB R _w (=laboratory value)
	Standard equipment	
	Drive set in E6/C0 anodized, including cover caps and stoppers	
	Circumferential sealing system in E6/C0 anodized and grey sealing profiles	
	Threshold made of stainless steel	
	Handle bars made of stainless steel	
	Additional equipment / Options	
	Running rail with retraction dampening	
	Locking	
	etc. according to the demands and the customer requests	

Edge design

- Solid wood edge band
- Solid wood inset edge band
- Powder-coated aluminium
- Plastic edge band
- PU-edge

Glazing cut-out

- Frame width 135 mm
- Frame width 110 mm minimum
- Circular glazing
- Special shapes

Door frame

- Aluminium frame
- Steel frame

Surface finish

- Laminates, HPL 0,8 mm
- Veneered, transparent lacquered
- Veneered, stained, transparent lacquered
- Powder-coated aluminium
- Coating on site / grounding foil

Customised, project-specific solutions possible

- standard
- optional

Further information can be found on our homepage www.Lindner-Group.com

